



SAFETY DATA SHEET - NZ
“NEW COAT HI TEMP PAINT – 350g AEROSOL”

SECTION 1 – PRODUCT IDENTIFICATION			
Product Name:	“NEW COAT HI TEMP PAINT – 350g AEROSOL		
Distributor:	Tollesbury Enterprises		
Address:	20A Peters Way, Silverdale, Auckland 0932		
Regular Phone No:	(09) 421 0191	FAX:	(09) 421 0192
Emergency Phone No:	021 873 434	Email:	info@tollesbury.co.nz
Substance:	Aerosol	Product Use:	Hi temperature paint
Product Code:	15-00		

SECTION 2 – HAZARDS IDENTIFICATION	
Classification of the substance or mixture	
Dangerous Goods	Classified as Dangerous Goods by the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land".
GHS Classification	Aerosol – Category 1 Eye Irritation – Category 2A Skin Sensitisation – Category 1A Specific Target Organ Toxicity (Single Exposure) – Category 3
EPA Classification	This material is classified as hazardous according to criteria of the New Zealand EPA
Group Standard	Aerosols (Flammable)
HSNO	HSR002515
Label elements	
GHS label pictograms	DANGER
Signal word	Flame, Exclamation Mark
Hazard statement(s)	
	Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or irritation. May cause allergic skin reaction.
Precautionary statement(s): General	
	Keep out of reach of children. Read label before use. In emergencies call 000.
Precautionary statement(s): Prevention	
	Keep away from heat – No smoking. Keep container tightly closed. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist, vapours or spray. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye protection and suitable respirator if required. Contaminated clothing should not be allowed out of the workplace.
Precautionary statement(s): Response	
	If medical advice is needed, have product container or label at hand. IF ON SKIN: If on skin wash with soap and water. If on skin or hair remove/take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a Poison Center or doctor if you feel unwell.
Precautionary statement(s): Storage	
	Store in accordance with local regulatory regulations, locked up, in a well ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C.



SAFETY DATA SHEET - NZ
“NEW COAT HI TEMP PAINT – 350g AEROSOL”

Precautionary statement(s): Disposal	
	Dispose of contents/container in accordance with local regulations.
Note	
IMPORTANT	This SDS and the Hazard Classifications contained therein, only apply to the product in its concentrated form, as supplied. Good hygiene and housekeeping practices should be adhered to.

SECTION 3 – INGREDIENTS		
Ingredients:	CAS Number:	Proportion:
Propane/n-butane propellant	68476-86-8 68476-85-7	30 - 60% w/w
Alkyd resin	Various	15 - 30 % w/w
Mineral turpentine	64742-88-7	15 - 30 % w/w
Aluminum Powder	7429-90-5	<1 % w/w
Methyl ethyl ketoxime	96-29-7	< 1% w/w
Additives	Various	< 1% w/w
NOTE: Ingredients determined not to be hazardous are present in concentrations that do not meet the criteria of a dangerous substance as defined in the current GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS) . Listed ingredients may be below the cut-off concentrations for classification as hazardous, but are listed for information purposes and for additive effects.		

SECTION 4 - EMERGENCY AND FIRST AID PROCEDURES	
Poisons Information	Poisons Information Centre in Christchurch, New Zealand can provide additional assistance for poisons. (New Zealand 0800 764 766).
First Aid Facilities	Normal washroom facilities.
Skin contact	Wash skin with plenty of water. Remove contaminated clothing and wash before re-use. Seek medical advice (e.g. doctor) if irritation, burning or redness develops.
Eye contact	Immediately irrigate with water for at least 20 minutes. Eyelids to be held open. Seek medical advice (e.g. ophthalmologist) if any irritation persists.
Ingestion	Do NOT induce vomiting. Rinse mouth thoroughly with water immediately. Give water to drink. If vomiting occurs, give further water to achieve effective dilution. Seek medical advice (e.g. doctor).
Inhalation	Remove victim to fresh air away from exposure - avoid becoming a casualty. Seek medical advice (e.g. doctor) if symptoms persist.
Advice to Doctor	Treat symptomatically. All treatments should be based on observed signs and symptoms of distress of the patient. Poisons Information Centre in each Australian State capital city or in Christchurch, New Zealand can provide additional assistance for scheduled poisons.
Aggravated Medical Conditions	None known.

SECTION 5 – FIRE FIGHTING MEASURES	
Fire and Explosion Hazards	Fire: Extremely flammable liquid. Product may form flammable/explosive vapour-air mixture during use. Hazardous combustion products: Carbon Monoxide, Carbon Dioxide and other possibly toxic gases and vapours on burning. Will float and can be reignited on surface water. The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Extinguishing Media	Carbon Dioxide, foam, dry powder.
Fire Fighting	If a significant quantity of this product is involved in a fire, call the fire brigade. Immediately evacuate the area of unnecessary personnel. Firefighters should wear safety boots, non-flammable overalls, gloves, hat, goggles, and self contained breathing equipment. Heating can cause expansion or decomposition of the material which can lead to the container(s) exploding. If safe to do so, remove container(s) from the path of the fire if it can be done



SAFETY DATA SHEET - NZ “NEW COAT HI TEMP PAINT – 350g AEROSOL”

	without risk. Do not scatter spilled material with high-pressure water streams. Dyke for later disposal. Use extinguishing agents for surrounding fire. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.
Flash Point	< -60°C (due to propellant)

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Emergency Procedures	<p>HAZCHEM code : 2YE</p> <p>2 = use water fog- in the absence of fog, a fine spray may be used to fight fires. Y = Yes – risk of violent reaction, recommend breathing apparatus for fire only, contain.</p> <ul style="list-style-type: none">• Shut off engine and electrical equipment off.• No smoking or naked lights within 50 metres.• Move people from immediate area; keep upwind.• Send messenger to notify fire brigade and police.• Tell them location, material quantity, UN number and emergency contact. Indicate condition of vehicle and damage or injuries observed.• Warn other traffic. <p>E = Consider evacuation.</p>
Occupational Release	<p>MINOR SPILLS</p> <p>Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Wipe up. If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely.</p> <p>MAJOR SPILLS</p> <p>Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Absorb or cover spill with sand, earth, inert materials or vermiculite. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal.</p>

SECTION 7 – HANDLING AND STORAGE





Handling	Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers closed at all times. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use.
Storage	Avoid all sources of ignition – (heat, sparks, static electricity, open flame). Use flameproof equipment and fittings to prevent flammability risk. Store in a well-ventilated area. Store in a cool, dry place and out of direct sunlight. Store away from incompatible substances i.e. strong oxidizing agents, acids or bases. Keep containers closed at all times – check regularly for leaks.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits	National Occupational Exposure Limits, as published by WorkSafe New Zealand: Time-weighted Average (TWA): None established for specific product. Exposure Limits of individual ingredients: Propane/n-butane propellant 1000ppm. Short Term Exposure Limit (STEL): None established for specific product.
------------------------	--



SAFETY DATA SHEET - NZ
“NEW COAT HI TEMP PAINT – 350g AEROSOL”

Engineering Controls	Use only in a well-ventilated area. Ensure airflow, where this product is used, is directed away from the operators. Ensure ventilation is adequate to maintain air concentrations below exposure standards. If this is not possible, use appropriate personal protective equipment (meeting the requirements of AS/NZS 1715 and AS/NZS 1716).
Personal Protective Equipment	Use good occupational work practice. The use of protective clothing and equipment depends upon the degree and nature of exposure. Final choice of appropriate protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. The following protective equipment should be available;
Eye Protection 	The use of safety glasses with side shield protection, goggles or face shield is recommended to handle in quantity, cleaning up spills, decanting, etc. Contact lenses pose a special hazard ; soft lenses may absorb irritants and all lenses concentrate them.
Skin Protection  	Overalls, work boots and elbow length gloves are recommended for handling the concentrated product (as per AS/NZS 2161, or as recommended by supplier) to handle in quantity, cleaning up spills, decanting, etc.
Protective Material Types	Material suitable for detergent contact – Butyl rubber, Natural Latex, Neoprene, PVC, and Nitrile.
Respirator 	No respirator should be required under normal conditions of use in well-ventilated areas (outdoors) provided air concentrations are below exposure standards. If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices. If the exposure limit is exceeded briefly, a full facepiece respirator with an organic vapour cartridge may be worn. For short elevated exposures, eg, spillages:- Appropriate organic vapour cartridge respirator as per the requirements of AS/NZS 1715 and AS/NZS 1716 (Respiratory protective devices). For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. Exposure Limit by more than ten times, air supplied apparatus should be used.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid compressed gas in aerosol can	Colour	Black
Odour	Hydrocarbon	Specific Gravity	1.0 - 1.35 @ 25 °C (for contents without propellant)
Boiling Point	149 - 199 °C (contents without propellant)	Freezing Point	Not available
Vapour Pressure	Not available	Vapour Density	Not available
Flash Point	< -60°C (for contents with propellant)	Flammable Limits	Not available
Water Solubility	Not soluble	pH	Not available
Volatile Organic Compounds (VOC)	40 – 60 % v/v	Coefficient of Water/Oil Distribution	Not available
Viscosity	Not available	Odour Threshold	Not available



SAFETY DATA SHEET - NZ

“NEW COAT HI TEMP PAINT – 350g AEROSOL”

Evaporation Rate	Not available	Per Cent Volatile	60 - 70 % v/v
------------------	---------------	-------------------	---------------

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability	Stable at normal temperatures and pressure.
Conditions to Avoid	Sources of heat and ignition, open flames.
Incompatible Materials	Oxidising agents, minerals acids, halogenated organic compounds.
Hazardous Decomposition	Product can decompose on combustion to form Carbon Monoxide, Carbon Dioxide, and other possibly toxic gases and vapours.
Hazardous Reactions	None known.

SECTION 11 – TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion

short term exposure	Harmful if swallowed. May cause irritation to the throat, mouth and digestive tract. Large doses may cause drowsiness and may lead to unconsciousness. Aspiration of liquid into lungs may cause serious (even fatal) pneumonitis.
long term exposure	No information available.

Skin contact

short term exposure	Irritant, both by contact and vapour. Prolonged exposure may result in dryness and cracking. If sprayed continuously on the skin it can cause frostbite.
long term exposure	Prolonged and repeated skin contact with undiluted solutions may induce eczematoid dermatitis.

Eye contact

short term exposure	Irritant, both by contact and vapour.
long term exposure	No information available.

Inhalation

short term exposure	On basis of ingredients: High concentrations of Propane can act as an asphyxiant. Vapour is irritating to mucous membranes and respiratory tract. Can cause dizziness, headaches, nausea and may lead to unconsciousness. Prolonged exposure to vapour may cause damage to the central nervous system. Intentional misuse by deliberately concentrating and breathing the contents can be harmful or fatal.
long term exposure	This product may contain traces of ethylbenzene and naphthalene derivatives. These products are classified as “possible human carcinogen (Group 2B)”. Prolonged exposure to vapours may cause somnolence and narcosis.

Carcinogen Status

SWA	No significant ingredient is classified as carcinogenic by SWA.
NTP	No significant ingredient is classified as carcinogenic by NTP.
IARC	No significant ingredient is classified as carcinogenic by IARC.
Respiratory sensitisation	Not expected to be a respiratory sensitizer.
Skin Sensitisation	May cause skin sensitization.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	See above – Inhalation (short term).
STOT-repeated exposure	See above – Inhalation (long term).
Aspiration Hazard	Aspiration of liquid into lungs may cause serious (even fatal) pneumonitis.

SECTION 12 – ECOLOGICAL INFORMATION

Eco-toxicity	
--------------	--



SAFETY DATA SHEET - NZ

“NEW COAT HI TEMP PAINT – 350g AEROSOL”

Product (as sold)	None available for specific product.
Persistence and degradability	Individual components stated to be biodegradable.
Bio accumulative potential	None available for specific product.
Mobility in soil	None available for specific product.
Other adverse effects	None available for specific product.
Environmental Protection	Expected to be toxic to aquatic organisms. Product not miscible with water. AS WITH ANY CHEMICAL PRODUCT, DO NOT DISCHARGE BULK QUANTITIES INTO DRAINS, WATERWAYS, SEWER OR ENVIRONMENT. Inform local authorities if this occurs.

SECTION 13 – DISPOSAL CONSIDERATIONS

Disposal	Dispose of material according to Local Authority Regulations or through a licensed waste contractor.
-----------------	--

SECTION 14 – TRANSPORT INFORMATION

Labels Required			
NZDG	Classified as Dangerous Goods by the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land".		
IMDG Marine Pollutant	No		
Land Transport (NZDG)			
UN Number	1950	Classification	Class 2.1
Shipping Name	AEROSOL, FLAMMABLE N.O.S.	Subsidiary Risk	none allocated
Hazchem Code	2YE	Packing Group	none allocated
Packaging Method	None allocated	Special Provisions	SP63, 190, 229, 277.
Segregation	None allocated		

SECTION 15 – REGULATORY INFORMATION

GHS Classification	This material is classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including the criteria of EPA regulations, New Zealand.
NZDG Code	Classified as Dangerous Goods by the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land".
AICS	All ingredients present on AICS.
HSNO	HSR002515

SECTION 16 – OTHER INFORMATION

Issue Date	3 February 2023
Version Number	V 5.0
Abbreviations and acronyms	<p>AICS: Australian Inventory of Chemical Substances.</p> <p>CAS Number: Chemical Abstracts Service Registry Number.</p> <p>GHS: Globally Harmonized System of Classification and Labelling of Chemicals</p> <p>HAZCHEM: An emergency action code of numbers and letters which gives information to emergency services.</p> <p>IARC: International Agency for Research on Cancer.</p> <p>SDS: Safety Data Sheet</p> <p>STEL: Short Term Exposure Limit.</p> <p>SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons.</p> <p>TWA: Time Weighted Average.</p>



SAFETY DATA SHEET - NZ
“NEW COAT HI TEMP PAINT – 350g AEROSOL”

	UN Number: United Nations Number.
Literature references	Global Harmonized System of Classification and Labelling of Chemicals (GHS) Safety Data Sheets – individual raw materials – Suppliers
<p>This SDS summarizes at the date of issue our best knowledge of the health and safety hazard information of this product, and in particular how to safely handle and use this product in the workplace. Since the supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this supplier.</p> <p>The SDS is valid for five years from date of issue but may be withdrawn and revised at any time prior to that date. All information contained in the Data Sheet is as accurate as possible at the time of issue. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. No expressed or implied warranties nor any responsibility for damages resulting from use of the information are given other than those implied mandatory by Commonwealth, State or Territory Legislation. If this product is to be re-packaged by others, it will be necessary for a new SDS to be generated by the re-packer.</p>	
End of SDS	